# B PAR360Z



#### **SPECSHEET**



### 7 x 60W RGBW LED zoom par

The B PAR360Z redefines the standards for IP-rated zoom pars with its 7x60W RGBW LED engine, capable of producing captivating colors and brilliant illumination. This fixture is distinguished by its rapid zoom capability and high saturation colors, providing dynamic lighting options for events and productions.

With an unmatched power-to-size ratio, the B PAR360Z offers creative freedom in designing lighting setups, ensuring that it can meet the demands of professionals looking for impactful and versatile lighting solutions. Its market-leading output and adaptability make it an essential tool for elevating lighting designs.



## **Physical**

Dimensions (WxHxD): 450 x 297 x 217 mm | 17.7 x 11.7 x 8.5 in Packaging dimensions (WxHxD): 510 x 360 x 265 mm | 20.7 x 14.1 x 10.4 in

 Net weight:
  $6.90 \text{ kg} \mid 15.2 \text{ lb}$  

 Gross weight:
  $7.60 \text{ kg} \mid 16.75 \text{ lb}$ 

Outer packaging gross weight: 13 kg | 28.66 lbs (2 Pcs)

Outer packaging dimensions: 575 x 380 x 540 mm | 22.6 x 15 x 21.25 in (2 Pcs)

## **Mounting options**

Hanging:  $1 \times 0$  mega bracket with  $2 \times 1/4$  turn quick-locks and  $1 \times 0$  M12 hole Second suspension:  $1 \times 0$  Moulded eye on the housing to pass a safety wire or carabiner

Standing: Double bracket | adjustable opening angle



**Control** 

Menu control: TFT display with 4 buttons
Control: DMX512, manual, master/slave

In/Link: XLR 5-pin

DMX Mode: 5/8/12/17 channels

Dimming: 8-bi

Dimming curve 3 curves (Inv. Square law, Linear, Square law)

Tilt locking system:

One hand tilt locking

**Optical** 

Beam angle: 4.3° - 45°

Colours: Red, Green, Blue and White

Refresh rate: 600 Hz - 9,600 Hz

Light Output @ 45°

2m: 4,200 lux 4m: 1157 lux 6m: 562 lux

**Electrical** 

Fixture rated power: 370W

LED engine: 7 x 60W SMD LED | RGBW 4 in 1

Input power: 100 - 240V ~ 50/60Hz | Auto switching power supply

In/Link: powerCON TRUE 1 | max. link current 10A

Power Factor: 0.94 LVI: n/a

**Environmental** 

Cooling: Electronic heat control

IP rating: IP65 Max. environment temperature: 40°

**Accessories** 

Included powerCON True 1, Omega bracket, Frost filter

**Optional** n/a

LUXIBEL